



**Advantages:**

- Small pitch offering short product transfers



Pages 4⇨7



Page 281



Pages 333⇨337

Chain - Ref.	Code	Material	Max. working load	Finish $\mu\text{m}$	Width L		G mm	RD mm	Weight Kg/m
					mm	inch			
SSE 515 K217	<b>10040</b>	EXTRA	5.200	0.3	55.0	2 1 <sup>1</sup> / <sub>64</sub>	1.6	100	2.3
SSE 515 K236	<b>10041</b>				60.0	2 2 <sup>7</sup> / <sub>64</sub>			2.4
SSE 515 K250	<b>10042</b>				63.5	2 1 <sup>1</sup> / <sub>2</sub>			2.5
SSE 515 K283	<b>10043</b>				72.0	2 2 <sup>7</sup> / <sub>32</sub>			2.7
SSE 515 K325	<b>10044</b>				82.5	3 1 <sup>1</sup> / <sub>4</sub>			2.9
SSE 515 K350	<b>10045</b>				88.9	3 1 <sup>1</sup> / <sub>2</sub>			3.0
SSE 515 K400	<b>10046</b>				101.6	4			3.3

**Standard length:** 120 pitches (10 ft. - 3.048 m)

Breaking Load according to Standard ISO 4348 - DIN 8153