



Advantages:

- Complete program to cover all applications
- All materials
- All sizes



Pages 4⇒7



Pages 266⇒270



Pages 333⇒337

Chain - Ref.	Code	Material	Max. working load	Finish μm	Flatness (max) mm	Polished hinges	Width L		G mm	RD mm	Weight Kg/m								
							mm	inch											
S 815 K300	10301	C 45	12.000	-	-	no	76.2	3	1.8	150	2.5								
S 815 K325	10302						82.5	3 1/4			2.6								
S 815 K350	10303						88.9	3 1/2			2.7								
S 815 K400	10304						101.6	4			3.0								
S 815 K450	10305						114.3	4 1/2			3.3								
S 815 K600	10306						152.4	6			4.2								
S 815 K750	10307						190.5	7 1/2			5.1								
SS 812 K325	10001	STANDARD	5.400	0.6	0.15	no	82.5	3 1/4	1.8	150	2.6								
SSR 812 K325	10007						82.5	3 1/4	2.8	75	2.5								
SS 812 K330	10034				1.8		150	0.2	83.8	3 1/8	2.6								
SS 812 K350	10002								88.9	3 1/2	2.7								
SS 812 K400	10003								101.6	4	3.0								
SS 812 K450	10004								114.3	4 1/2	3.3								
SS 812 K600	10005								152.4	6	4.2								
SS 812 K750	10006								190.5	7 1/2	5.1								
SSE 815 K300	10033							EXTRA PLUS	6.000	0.3	0.15	no	76.2	3	1.8	150	2.5		
SSE 815 K325	10009												82.5	3 1/4			2.6		
SSE 815 K330	10032	1.8	150	0.2	83.8	3 1/8	2.6												
SSE 815 K350	10010				88.9	3 1/2	2.7												
SSE 815 K400	10011				101.6	4	3.0												
SSE 815 K450	10012				114.3	4 1/2	3.3												
SSE 815 K600	10013				152.4	6	4.2												
SSE 815 K750	10014				190.5	7 1/2	5.1												
SSE 815 K325 HB	10036			EXTRA PLUS HB	6.000	0.3	0.15				no		82.5	3 1/4			1.8	150	2.5
SSE 815 K330 HB	10037												83.8	3 1/8					2.6
SSA 815 K325	10016	AUSTIC	5.300	0.3	0.15	no	82.5	3 1/4	1.8	150	2.6								
SSA 815 K330	10035						1.8	150			0.2	83.8	3 1/8	2.6					
SSA 815 K350	10017				88.9							3 1/2	2.7						
SSA 815 K400	10018				101.6							4	3.0						
SSA 815 K450	10019				114.3							4 1/2	3.3						
SSA 815 K600	10020				152.4						6	4.2							
SSA 815 K750	10021				190.5						7 1/2	5.1							

Standard length: 80 pitches (10 ft. - 3.048 m)

Breaking Load according to Standard ISO 4348 - DIN 8153