



Advantages:

- The best choice for the most demanding applications, like pressureless combiners and high speed applications
- Improved flatness
- Optimum product stability

812L - 815L STRAIGHT RUNNING CHAINS SINGLE HINGE



Pages 4⇒7



Pages 266⇒270



Pages 333⇒337

Chain - Ref.	Code	Material	Max. working load	Finish μm	Flatness (max) mm	Polished hinges	Width L		G mm	RD mm	Weight Kg/m
							mm	inch			
SSL 812 K325	10001L	STANDARD	5.400	0.6	0.1	no	82.5	3 1/4	1.5	150	2.55
SSEL 815 K325	10009L	EXTRA PLUS	6.000	0.3							
SSEL 815 K325 HB	10036L	EXTRA PLUS HB									

815L SPEED - LINE STRAIGHT RUNNING CHAINS SINGLE HINGE

Chain - Ref.	Code	Material	Max. working load	Finish μm	Flatness (max) mm	Polished hinges	Width L		G mm	RD mm	Weight Kg/m
							mm	inch			
SPCL 815 K325	10080L	EXTRA PLUS	6.000	0.3	0.1	yes	82.5	3 1/4	1.5	150	2.55
SPCL 815 K330	10081L			83.8			3 19/64	2.60			
SPSL 815 K325	10085L			82.5			3 1/4	2.55			
SPSL 815 K330	10086L			83.8			3 19/64	2.60			
SPCL 815 K325 HB	10090L	EXTRA PLUS HB	6.000	0.3	0.1	yes	82.5	3 1/4	1.5	150	2.55
SPCL 815 K330 HB	10091L			83.8			3 19/64	2.60			
SPSL 815 K325 HB	10095L			82.5			3 1/4	2.55			
SPSL 815 K330 HB	10096L			83.8			3 19/64	2.60			

Standard length: 80 pitches (10 ft. - 3.048 m)

Breaking Load according to Standard ISO 4348 - DIN 8153