



Tipo Type	Dimensioni mm/pollici Dimensions mm/inch										Bull. fiss. Bolt Size mm/inch	Coefficienti di carico (N) Load ratings (N)		Cuscinetto Bearing	Supporto Housing	Peso Weight (kg)
	d	h	a	e	b	g	l	w	B	n		Dinamico C Dynamic C	Statico C ₀ Static C ₀			
UCPA201 UCPA201-8	12 3/4	30,2 1 1/16	76 3	52 2 3/4	40 1 9/16	15 1 1/2	11 7/16	62 2 7/16	31 1,2205	12,7 0,500	M10 3/8	12 200	6 350	UC201 UC201-8	PA204	0,60 0,59
UCPA202 UCPA202-9 UCPA202-10	15 9/16 5/8	30,2 1 1/16	76 3	52 2 3/4	40 1 9/16	15 1 1/2	11 7/16	62 2 7/16	31 1,2205	12,7 0,500	M10 3/8	12 200	6 350	UC202 UC202-9 UC202-10	PA204	0,59 0,59 0,59
UCPA203 UCPA203-11	17 1 1/16	30,2 1 1/16	76 3	52 2 3/4	40 1 9/16	15 1 1/2	11 7/16	62 2 7/16	31 1,2205	12,7 0,500	M10 3/8	12 200	6 350	UC203 UC203-11	PA204	0,58 0,57
UCPA204 UCPA204-12	20 3/4	30,2 1 1/16	76 3	52 2 3/4	40 1 9/16	15 1 1/2	11 7/16	62 2 7/16	31 1,2205	12,7 0,500	M10 3/8	12 200	6 350	UC204 UC204-12	PA204	0,56 0,56
UCPA205 UCPA205-13 UCPA205-14 UCPA205-15 UCPA205-16	25 1 3/16 7/8 15/16 1	36,5 1 1/16	84 3 5/16	56 2 1 3/4	38 1 1/2	15 1 1/2	12 1 1/2	72 2 5 3/4	34,1 1,3425	14,3 0,563	M10 3/8	13 300	7 500	UC205 UC205-13 UC205-14 UC205-15 UC205-16	PA205	0,83 0,87 0,86 0,84 0,83
UCPA206 UCPA206-17 UCPA206-18 UCPA206-19 UCPA206-20	30 1 1/16 1 1/8 1 3/16 1 1/4	42,9 1 11/16	94 3 4 5/8	66 2 1 3/4	50 1 3 1/2	18 1 1/2	12 1 1/2	84 3 1/4	38,1 1,5000	15,9 0,626	M14 1/2	18 600	10 800	UC206 UC206-17 UC206-18 UC206-19 UC206-20	PA206	1,12 1,15 1,14 1,12 1,11
UCPA207 UCPA207-20 UCPA207-21 UCPA207-22 UCPA207-23	35 1 1/4 1 5/16 1 3/8 1 7/16	47,6 1 7/8	110 4 1 3/4	80 3 1/2	55 2 1 1/4	20 1 1/2	13 1 1/4	95 3 4 7/8	42,9 1,6890	17,5 0,689	M14 1/2	24 500	14 600	UC207 UC207-20 UC207-21 UC207-22 UC207-23	PA207	1,48 1,54 1,51 1,48 1,45
UCPA208 UCPA208-24 UCPA208-25	40 1 1/2 1 9/16	49,2 1 15/16	116 4 9/16	84 3 1/4	58 2 1 1/2	20 1 1/2	13 1 1/4	100 3 1 1/2	49,2 1,9370	19 0,748	M14 1/2	27 700	17 000	UC208 UC208-24 UC208-25	PA208	1,89 1,93 1,90
UCPA209 UCPA209-26 UCPA209-27 UCPA209-28	45 1 5/8 1 11/16 1 3/4	54,2 2 1/16	120 4 3 3/8	90 3 3 3/4	60 2 3 3/4	25 1 1/2	13 1 1/4	108 4 1/4	49,2 1,9370	19 0,748	M14 1/2	31 000	19 500	UC209 UC209-26 UC209-27 UC209-28	PA209	1,98 2,08 2,04 2,00
UCPA210 UCPA210-29 UCPA210-30 UCPA210-31 UCPA210-32	50 1 13/16 1 7/8 1 15/16 2	57,2 2 1/4	130 5 1/8	94 3 4 5/8	64 2 3 3/4	25 1 1/2	14 1 1/4	116 4 9/16	51,6 2,0315	19 0,748	M16 5/8	33 500	22 500	UC210 UC210-29 UC210-30 UC210-31 UC210-32	PA210	2,16 2,28 2,23 2,18 2,14
UCPA211 UCPA211-32 UCPA211-33 UCPA211-34 UCPA211-35	55 2 2 1/16 2 1/8 2 3/16	63,5 2 1/2	140 5 3 3/8	104 4 1 1/2	66 2 1 1/2	25 1 1/2	14 1 1/4	125 4 5 9/16	55,6 2,1890	22,2 0,874	M16 5/8	41 500	28 000	UC211 UC211-32 UC211-33 UC211-34 UC211-35	PA211	3,26 3,41 3,35 3,30 3,24
UCPA212 UCPA212-36 UCPA212-37 UCPA212-38 UCPA212-39	60 2 1/4 2 5/16 2 3/8 2 7/16	69,9 2 3/4	150 5 2 5/8	114 4 3 1/4	68 2 4 3/4	25 1 1/2	15 1 1/4	138 5 1/2	65,1 2,5630	25,4 1,000	M16 5/8	50 000	34 500	UC212 UC212-36 UC212-37 UC212-38 UC212-39	PA212	4,19 4,32 4,24 4,17 4,10
UCPA213 UCPA213-40 UCPA213-41	65 2 1/2 2 9/16	76,2 3	160 6 1 1/4	124 4 7/8	70 2 3/4	25 1 1/2	15 1 1/4	150 5 5 3/8	65,1 2,5630	25,4 1,000	M16 5/8	54 700	38 000	UC213 UC213-40 UC213-41	PA213	- - -

Disponibile in acciaio inox Supporto: AISI 304 - Cuscinetto: AISI 440C
Disponibile su richiesta con cuscinetto SA (SAPA)

Available stainless steel Housing: AISI 304 - Bearing: AISI 440C
Available under request with SA bearing (SAPA)